

Lesson 20

Reshape the structure of tensor

```
x = tf.constant([1,2,3,4,5,6])  
print(x)
```

```
tf.Tensor([1 2 3 4 5 6], shape=(6,), dtype=int32)
```

```
[ 1, 2, 3, 4, 5, 6]
```

Reshape the structure of tensor

```
x = tf.constant([1,2,3,4,5,6])  
print(x)
```

```
tf.Tensor([1 2 3 4 5 6], shape=(6,), dtype=int32)
```

```
[ 1, 2, 3, 4, 5, 6]
```

```
x = tf.constant([1,2,3,4,5,6], shape=(2,3))  
print(x)
```

```
tf.Tensor(  
[[1 2 3]  
 [4 5 6]], shape=(2, 3), dtype=int32)
```

```
[ 1, 2, 3]  
[ 4, 5, 6]
```

Reshape the structure of tensor

```
x = tf.constant([1,2,3,4,5,6])  
print(x)
```

```
tf.Tensor([1 2 3 4 5 6], shape=(6,), dtype=int32)
```

```
[ 1, 2, 3, 4, 5, 6]
```

```
x = tf.constant([1,2,3,4,5,6], shape=(2,3))  
print(x)
```

```
tf.Tensor(  
[[1 2 3]  
 [4 5 6]], shape=(2, 3), dtype=int32)
```

```
[ 1, 2, 3]  
[ 4, 5, 6]
```

```
[ 1, 2]  
[ 3, 4]  
[ 5, 6]
```

Reshape the structure of tensor

```
x = tf.constant([1,2,3,4,5,6])  
print(x)
```

```
tf.Tensor([1 2 3 4 5 6], shape=(6,), dtype=int32)
```

```
[ 1, 2, 3, 4, 5, 6]
```

```
x = tf.constant([1,2,3,4,5,6], shape=(2,3))  
print(x)
```

```
tf.Tensor(  
[[1 2 3]  
 [4 5 6]], shape=(2, 3), dtype=int32)
```

```
[ 1, 2, 3]  
[ 4, 5, 6]
```

```
tf.reshape(x, (3,2))
```

```
<tf.Tensor: shape=(3, 2), dtype=int32, numpy=  
array([[1, 2],  
       [3, 4],  
       [5, 6]])>
```

```
[ 1, 2]  
[ 3, 4]  
[ 5, 6]
```

Flatten the tensor

```
[ 1, 2, 3, 4]  
[ 5, 6, 7, 8]
```



```
[ 1, 2, 3, 4, 5, 6, 7, 8]
```

```
x = tf.constant([[1,2,3,4],[5,6,7,8]], shape=(8))  
print(x)
```

```
tf.Tensor([1 2 3 4 5 6 7 8], shape=(8,), dtype=int32)
```

Flatten the tensor

```
[ 1, 2, 3, 4]  
[ 5, 6, 7, 8]
```



```
[ 1, 2, 3, 4, 5, 6, 7, 8]
```

```
x = tf.constant([[1,2,3,4],[5,6,7,8]], shape=(8))  
print(x)
```

```
tf.Tensor([1 2 3 4 5 6 7 8], shape=(8,), dtype=int32)
```

```
x = tf.constant([[1,2,3,4],[5,6,7,8]])  
tf.reshape(x, (8))
```

```
<tf.Tensor: shape=(8,), dtype=int32, numpy=array([1, 2, 3, 4, 5, 6, 7, 8])>
```

Reshape the tensor with (-1)

```
x = tf.constant([[1,2,3,4],[5,6,7,8]])  
print(x)
```

```
tf.Tensor(  
[[1 2 3 4]  
 [5 6 7 8]], shape=(2, 4), dtype=int32)
```

```
tf.reshape(x, (-1))
```

```
<tf.Tensor: shape=(6,), dtype=int32, numpy=array([1, 2, 3, 4, 5, 6])>
```

```
[ 1, 2, 3, 4]  
[ 5, 6, 7, 8]
```

```
[ 1, 2, 3, 4, 5, 6, 7, 8]
```


More on (-1) shape

```
x = tf.constant([[1,2,3,4],[5,6,7,8]])  
print(x)
```

```
tf.Tensor(  
[[1 2 3 4]  
 [5 6 7 8]], shape=(2, 4), dtype=int32)
```

```
tf.reshape(x, (4,-1))
```

```
<tf.Tensor: shape=(4, 2), dtype=int32, numpy=  
array([[1, 2],  
       [3, 4],  
       [5, 6],  
       [7, 8]])>
```

```
[ 1, 2, 3, 4]  
[ 5, 6, 7, 8]
```

```
[ 1, 2]  
[ 3, 4]  
[ 5, 6]  
[ 7, 8]
```

More on (-1) shape

```
x = tf.constant([1,2,3,4,5,6,7,8])  
tf.reshape(x, (2,-1,2))
```

```
<tf.Tensor: shape=(2, 2, 2), dtype=int32, numpy=  
array([[ [1, 2],  
        [3, 4]],  
       [[5, 6],  
        [7, 8]])>
```

```
[ [1, 2]  
  [3, 4]  
 [ [5, 6]  
   [7, 8]
```

More on (-1) shape

```
x = tf.constant([1,2,3,4,5,6,7,8])  
tf.reshape(x, (2,-1,2))
```

```
<tf.Tensor: shape=(2, 2, 2), dtype=int32, numpy=  
array([[ [1, 2],  
        [3, 4]],  
       [[5, 6],  
        [7, 8]])>
```

```
x = tf.constant([[1,2,3,4],[5,6,7,8]])  
tf.reshape(x, (-1,2,2))
```

```
<tf.Tensor: shape=(2, 2, 2), dtype=int32, numpy=  
array([[ [1, 2],  
        [3, 4]],  
       [[5, 6],  
        [7, 8]])>
```

```
[ [ 1, 2]  
  [ 3, 4]  
 [ [ 5, 6]  
  [ 7, 8]
```

More on (-1) shape

```
x = tf.constant([1,2,3,4,5,6,7,8])  
tf.reshape(x, (2,-1,2))
```

```
<tf.Tensor: shape=(2, 2, 2), dtype=int32, numpy=  
array([[[1, 2],  
        [3, 4]],  
       [[5, 6],  
        [7, 8]])])>
```

```
[[1, 2]  
 [3, 4]  
 [[5, 6]  
 [7, 8]]
```

```
x = tf.constant([[1,2,3,4],[5,6,7,8]])  
tf.reshape(x, (-1,2,2))
```

```
<tf.Tensor: shape=(2, 2, 2), dtype=int32, numpy=  
array([[[1, 2],  
        [3, 4]],  
       [[5, 6],  
        [7, 8]])])>
```

```
x = tf.constant([[1,2,3,4],[5,6,7,8]])  
tf.reshape(x, (2,2,-1))
```

```
<tf.Tensor: shape=(2, 2, 2), dtype=int32, numpy=  
array([[[1, 2],  
        [3, 4]],  
       [[5, 6],  
        [7, 8]])])>
```

Summary

We have learnt

- How to create a variable tensor?
- How to convert a constant tensor to a variable tensor, and vice versa?
- How to reshape a tensor?