

# L<sup>A</sup>T<sub>E</sub>X WORKSHOP

## AN INTRODUCTION TO L<sup>A</sup>T<sub>E</sub>X

---

Rakesh Jana

`j.rakesh@iitg.ernet.in`

Date: 2017/09/09

Research Scholar

Department of Mathematics

IIT Guwhati



1. Header
2. Reference
3. Page Numbering

HEADER

---

# Fancy Header

- To customize the footer and header in your document use `\usepackage{fancyhdr}` in your preamble of your document
- After that put `\pagestyle{fancy}` to set default fancy page style.
- `\fancyhf{}` clears any predefined header and footer control.
- `\rhead{text}` right side of the header.
- `\lhead{text}` left side of the header.

Similarly one can define `\chead{text}`, `\lfoot{text}`, `\rfoot{text}`, etc.

`\rfoot{Page \thepage}` : `\thepage` the represent corresponding page number.

# Fancy Header

There are very good way to define **header** and **footer** in two-sided document. Try the following code:

```
\usepackage{fancyhdr}
\pagestyle{fancy}
\fancyhf{}
\fancyhead[LE,RO]{Share\LaTeX}
\fancyhead[RE,LO]{Guides and tutorials}
\fancyfoot[CE,CO]{\leftmark}
\fancyfoot[LE,RO]{\thepage}
```

# Fancy Header

There are very good way to define **header** and **footer** in two-sided document. Try the following code:

```
\usepackage{fancyhdr}
\pagestyle{fancy}
\fancyhf{}
\fancyhead[LE,RO]{Share\LaTeX}
\fancyhead[RE,LO]{Guides and tutorials}
\fancyfoot[CE,CO]{\leftmark}
\fancyfoot[LE,RO]{\thepage}
```

- **E**: for Even side Page
- **O**: for Odd side Page
- **R**: for Right Side
- **L**: for left Side
- **C**: for center

There are other options available like 7

- `\thepage`: adds number of the current page
- `\thechapter`: adds number of the current Chapter
- `\thesection`: adds number of the current section
- `\chaptername`: adds name of the current chapter
- `\rightmark`: Adds name and number of the current top-level structure (for example, Chapter for reports and books classes; Section for articles )

# REFERENCE

---



- The `hyperref` package creates hyperlinks within the document by making `references` and `citations` `clickable`.
- `\usepackage{hyperref}` use in preamble of your document.
- `\hypersetup{opt1, opt2 }` enables more manual control.

Some options are following which can be used in `\hypersetup`

<code>\colorlinks=true</code>	Links will be coloured, (default colour is red)
<code>\linkcolor=blue</code>	Internal links, those generated by cross-referenced elements, are displayed in blue.
<code>\filecolor=magenta</code>	Links to local files will be shown in magenta colour.
<code>\urlcolor=cyan</code>	Links to web sites are set to cyan colour.

- `\url{http://www.iitg.ac.in}` using this you will see `http://www.iitg.ac.in` in your document but if you click that word it will open `http://www.iitg.ac.in` in your browser.

There are many other option available under `hypersetup`. (See `hyperref` manual)

- `\url{http://www.iitg.ac.in}` using this you will see `http://www.iitg.ac.in` in your document but if you click that word it will open `http://www.iitg.ac.in` in your browser.
- `\href{http://www.iitg.ac.in}{Something Linky}` using this you will see only **Something Linky** in your document but if you click that word it will open in your browser.

There are many other option available under `hypersetup`. (See `hyperref` manual)

# PAGE NUMBERING

---

# Table of Content

- `\tableofcontents` will automatically create Sections, subsections and chapters are included in the table of contents.

`\renewcommand*\contentsname{Summary}` will write **Summary** instead of the default name **Table of Contents**.

# Table of Content

- `\tableofcontents` will automatically create Sections, subsections and chapters are included in the table of contents.
- You can also include manually entry by  
`\addcontentsline{toc}{section}{Unnumbered Section}`

`\renewcommand*\contentsname{Summary}` will write **Summary** instead of the default name **Table of Contents**.

THANK  
YOU